

## TITAN FORMULA SAE 15W-40

High Performance Engine Oil specially for all normally aspirated and turbocharged gasoline and diesel engines in passenger cars operated under normal conditions.

### Description

TITAN FORMULA SAE 15W-40 is a conventional all-year engine oil with a modern formulation for petrol and diesel engines with or without turbochargers in cars, LCV's, trucks, buses and machinery. TITAN FORMULA SAE 15W-40 is a high performance and low cost engine oil in one, developed for standard drain intervals.

### Application

TITAN FORMULA 15W-40 is preferably used in older passenger car engines, distribution traffic for LCV's and according OEM recommendation in all other application. Gear and gear hydraulic systems in vehicles and machinery for which HD multigrade engine oils are recommended can perfectly use TITAN FORMULA SAE 15W-40. TITAN FORMULA SAE 15W-40 is miscible and compatible with conventional branded engine oils. However, mixing with other engine oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN FORMULA SAE 15W-40. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

### Advantages/Benefits

- Very good wear protection
- Excellent anti corrosion performance
- Excellent engine cleanliness
- Sustainable lubrication also at more severe running conditions
- Can be used for engines with 3 way catalyst
- Low oil consumption
- Can be used for engines with hydraulic lifters/tappets

### Specifications

- ACEA A3/B3
- API SL

### Approvals

- MB-APPROVAL 229.1

### FUCHS Recommendations

- API CG-4
- FIAT 9.55535-D2/G2
- VW 501 01/505 00

PI60068e, PMA, 06.06.2019, Page 1

## TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.887 g/ml
SAE Grade	SAE J300	15W-40
Kinematic Viscosity at 40°C	DIN 51562-1	104 mm <sup>2</sup> /s
Kinematic Viscosity at 100°C	DIN 51562-1	13.9 mm <sup>2</sup> /s
Viscosity index		133
HTHS	CEC L-036-90	≥ 3.5 mPa*s
Pour point		-42 °C
Sulphated ash	ASTM D874	≥ 0.9 and ≤ 1.5 % m/m
Product dyeing	DIN 10964	none

PI60068e, PMA, 06.06.2019, Page 2

**FUCHS LUBRICANTS (UK) PLC**  
New Century Street, Hanley  
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel +44-1782 -20 37 00  
Fax +44-1782 -20 20 73  
contact-uk@fuchs-oil.com



Health, Safety and Environment - information is provided for products in the relevant Safety Data Sheet. This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products.

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products